

YOUR SOIL - OUR PASSION

DALBO®

FRONTFLEX

150-600



MADE IN  DENMARK

FRONTFLEX

150-600





WORKING WIDTH
1.50-6.00 M



TRANSPORT WIDTH
1.50-4.00 M



RING SIZE
50-60 CM



HORSEPOWER
> 30 HP



WEIGHT
715-2.070 KG

FRONTFLEX is a flexible and compact front-mounted roller, designed for efficient soil packing and seedbed preparation in a single pass. It is available both as a single section for smaller farms and as a 3-part foldable model for larger areas – without compromising on strength and work quality.



WHY CHOOSE FRONTFLEX?

- » Optimal productivity with working width equal to transport width
- » Robust construction in quality and high-strength steel
- » Flexible configurations with cracker board or 2-bullet cultivator
- » Easy maneuvering with unique 3-point suspension
- » Fully hydraulic folding and unfolding for quick change between transport and work
- » Option for front and rear mounting
- » Efficient soil packing and seedbed preparation in a single pass

TECHNICAL DATA

	150 M	260 M	300 M	400 M	450 M HYDRAULIC FOLDABLE	600 M HYDRAULIC FOLDABLE
Transport width	1.50 m	2.60 m	3.00 m	4.00 m	3.00 m	3.00 m
50 cm SNOWFLAKE® - weight kg/number of rings	1.000/29	1.155/47	1.290/55	1.640/75	-	-
55 cm SNOWFLAKE® - weight kg/number of rings	850/29	1.365/47	1.525/55	1.940/75	-	-
60 cm SNOWFLAKE® - weight kg/number of rings	1.165/29	1.540/47	1.730/55	-	-	-
53 cm Crosskill - weight kg/number of rings	715/15	975/25	1.075/29	1.215/37	-	-
60 cm Crosskill - weight kg/number of rings	920/15	1.240/25	1.380/29	1.750/37	-	-
50 cm Cross Combi - weight kg/number of rings	800/25	1.260/43	1.255/46	1.770/66	-	-
55 cm Cross Combi - weight kg/number of rings	1.005/25	1.450/43	1.485/46	2.070/66	-	-
50 cm Cross Combi light - weight kg/number of rings	-	-	-	-	1.945- 2.000/70*	2.385- 2.460/94*
Mechanical cracker board 45x10 mm tines - weight kg/number of tines	115/18	160/18	175/22	200/28		
Hydraulic cracker board 45x10 mm tines - weight kg/number of tines	100/10	130/18	150/22	-		
Hydraulic cracker board 80x10 mm tines - weight kg/number of tines	105/-	135/14	250/16	-		
Power requirement min.	30 HP	40 HP	50 HP	60 HP	60 HP	70 HP
Hydraulic connections	-	-	-	-	1xDA	1xDA

*Weight depends on choice of bearing position

ROLLER RINGS

SNOWFLAKE®. This ring is used in combination with intermediate serrated rings and is suitable for most purposes, both before and after sowing. It is especially suitable for rolling after sowing as well as maintenance of established grass fields. The Cross Combi rings are very suitable for seedbed preparation

in combination with the cracker board. The aggressive profile of the rings is good for crushing and leveling uneven soil. Crosskill. This ring type is primarily used for seedbed preparation and leaves the soil loose on top and firmer just below the surface, which is optimal for sowing.



CULTIVATOR SECTION

A 2-row cultivator section in front of the packer helps break down clods and levels the soil perfectly, making the packer much more efficient and leaving a completely uniform surface and structure.

The 2-row cultivator is supplied as standard with hydraulic depth adjustment, so the depth can be set very precisely from inside the tractor.



CRACKER BOARD

Hydraulically adjustable cracker board, consisting of heavy-duty 80 mm spring tines with 100 x 12 mm bent wear parts or 45 mm spring tines with 50 x 10 mm bent wear parts. This makes the cracker board perfect for crushing clods and leveling the soil, leaving the soil loose, even, and in perfect structure for the packer section.

To achieve optimal working conditions for, and thus the effect of, the cracker board, we recommend a working speed of 8-10 km/h.



EQUIPMENT

	150 M	260 M	300 M	400 M	450 M HYDRAULIC FOLDABLE	600 M HYDRAULIC FOLDABLE
Fully hydraulic folding and unfolding	-	-	-	-	■	■
Robust frames of quality steel and high-strength steel	■	■	■	■	■	■
Mounting for front and rear installation	■	■	■	■	■	■
Manual transport lock	■	■	■	■	-	-
Jack	■	■	■	■	■	■
Mechanically adjustable cracker board	□	□	□	□	-	-
Hydraulic adjustable cracker board	□	□	□	-	-	-
2-row cultivator	-	□	□	-	-	-
LED lighting	□	□	□	□	□	□

■ Standard □ Option - Not possible

DALBO®

Also available from DALBO



POWERROLL 3-sec 450-950



POWERROLL 5-sec 1030-1830



FRONT PRESSES 150-600



MAXIROLL 530-1230



MAXIROLL GREENLINE 630-830



MAXICUT 600-920



CULTIMAX 650-1000



ROLLOMAXIMUM 620-1240



ROLLOMASTER 300-600



TRIMAX 300-630



POWERCHAIN 500-1200



SUBSOILER M Profi

DALBO A/S, Bindeballevej 69, DK-7183 Randbøl
Tel.: +45 75 88 35 00, info@dalboagro.com, www.dalboagro.com