

YOUR SOIL - OUR PASSION

DALBO®

MAXIROLL

530-1230



MADE IN  DENMARK

MAXIROLL

530-1230





WORKING WIDTH
5.30-12.30 M



TRANSPORT WIDTH
2.50-3.00 M



RING SIZE
50-65 CM



HORSEPOWER
> 90 HP



WEIGHT
2.290-13.480 KG

MAXIROLL is a versatile system roller that, with its unique roller frame design and high ground clearance, can be combined with a wide range of effective front tools. The result is high productivity and better yields – especially on medium to heavy soil types.



WHY CHOOSE MAXIROLL?

- » Unique frame design with high ground clearance for flexible implement combination
- » Can be adapted to many tasks: rolling, stubble cultivation, grass care, and seedbed preparation
- » Increases efficiency and reduces the need for multiple machines
- » Save time and operating costs compared to conventional solutions
- » Ideal for varied soil types and changing tasks

TECHNICAL DATA

	530 T	630 T	760 T	830 T	830 HD T	950 T	1230 HD T
Transport width	2.50 m	2.50 m	2.50 m	2.50 m	3.00 m	3.00 m	3.00 m
50 cm SNOWFLAKE® - weight kg/number of rings	2.775/109	3.640/129	4.185/157	4.450/165	-	5.730/197	10.920/252
55 cm SNOWFLAKE® - weight kg/number of rings	3.205/109	4.240/129	4.935/157	5.210/165	5.550/167	6.645/197	11.730/252
60 cm SNOWFLAKE® - weight kg/number of rings	3.855/109	4.750/129*	5.595/157	5.970/167	6.300/165	7.365/197	12.750/252
65 cm SNOWFLAKE® - weight kg/number of rings	3.960/108	5.110/126*	5.990/148	-	6.900/162	-	13.480/252
53 cm Crosskill - weight kg/number of rings	2.290/55	3.150/63	3.685/79	3.900/83	-	5.130/99	9.900/128
60 cm Crosskill - weight kg/number of rings	2.975/55	3.970/63	4.785/79	5.050/83	-	6.425/99	11.300/128
50 cm Cross Combi - weight kg/number of rings	2.900/92	3.590/114	4.375/134	4.555/83	-	5.700/174	11.070/222
55 cm Cross Combi - weight kg/number of rings	3.32092	4.510/114	5.070/134	5.275/83	5.600/142	6.770/174	12.000/222
60 cm bogie Cross Combi - weight kg/number of rings	-	4.900/67*	-	-	6.300/83	-	-
60 cm T-ring - weight kg/number of rings	-	2.355/45	-	-	-	-	-
60 cm bogie T-Ring - weight kg/number of rings	-	3.555/67	-	-	4.600	-	-
Wheels	300/80x 15.3	300/80x 15.3	400/60x 15.5	400/60x 15.5	400/60x 15.5	400/60x 15.5	700/40x 22.5
Power requirement min.	90 HP	100 HP	110 HP	120 HP	120 HP	130 HP	140 HP
Hydraulic connections	1xSA+1xDA	1xSA+1xDA	1xSA+1xDA	1xSA+1xDA	1xSA+1xDA	1xSA+1xDA	1xSA+2xDA

* Wheels: 400/60x15.5 TWIN

ROLLER RINGS

SNOWFLAKE® used with intermediate serrated rings and suitable for most applications before and after sowing. Particularly effective for grassland maintenance and, together with the hydraulic cracker board, for leveling cloddy soil. Cross Combi Rings are ideal for seedbed preparation, especially when combined with a hydraulic cracker board. The aggressive ring profile and knife roller provide excellent cutting and crushing of heavy residues such as maize stubble and are highly effective against the corn borer beetle. Combined with a harrow, they are also well suited for grassland aeration and rolling. For heavy soils, the MAXIROLL 630 and 830 HD can be equipped with bogie-mounted Cross Combi rings, whose increased weight ensures efficient clod crushing. Crosskill Rings are primarily designed for seedbed preparation, leaving the soil loose on top and firm below the surface for optimal sowing conditions. For MAXIROLL 630 and 830 HD models, T-rings are also available and are particularly suitable for light and sandy soils.suitable for use on light and sandy soil types.



KNIFE ROLLER

A knife roller section helps you cut and crush thick stubble for faster and better decomposition and is a perfect match with the aggressive ring profile of the Cross Combi rings. The effectiveness of the knife roller and Cross Combi rings is only surpassed by our MAXICUT knife roller.



HARROW/MOLE HILL BOARD

The adjustable mole hill board is primarily designed to increase the roller's performance for leveling, rolling, and maintenance of grass fields together with a 2-bullet harrow.



CRACKER BOARD

Hydraulically operated and adjustable cracker board, which consists of robust 80 mm spring tines with 100 x 12 mm wearing parts, making it perfect for crushing clods and leveling the soil, thus leaving the soil loose, even, and in perfect structure for the roller section. The board is suspended in a parallelogram, which makes angle and working depth independent of each other. When you use the MAXIROLL only for rolling, the cracker board can be lifted hydraulically, which provides increased usability and versatility. The cracker board requires an extra double-acting hydraulic outlet on the tractor. To achieve optimal working conditions for, and thus the effect of the cracker board, we recommend a working speed of 8-10 km/h.



CULTIVATOR SECTION

The 1-, 2-, and 3-bullet cultivator tools with straight tines or goosefoot tines transform the MAXIROLL into a stubble tool or a seedbed cultivator.



HARROW SECTION

We offer many different harrow tools that enable you to perform a wide range of tasks from simple grass field aeration to cultivating in stubble.



WHEEL TRACK ERADICATOR

The use of wheel track eradicators helps you create an even and loose soil structure after the tractor wheels, especially when using heavy tractors with single wheel sets on light to medium soil types.



SEEDING EQUIPMENT

If you are looking for an ideal solution for the maintenance of grass areas, sowing of catch crops and similar, our seeding equipment helps you save valuable time and increase efficiency.



EQUIPMENT

	530 T	630 T	760 T	830 T	830 HD T	950 T	1230 HD T
Fully hydraulic folding and unfolding	■	■	■	■	■	■	■
Automatic transport lock	■	■	■	■	■	■	■
Hydraulic weight distribution	■	■	■	■	■	■	■
DUOFLEX	■	■	■	■	■	■	■
Robust frames of quality steel and high-strength steel	■	■	■	■	■	■	■
Ø60 mm axles of high-strength steel	■	■	■	■	■	■	■
Robust flange bearings	■	■	■	■	■	■	■
Removable jack	■	■	■	■	■	■	■
Hydraulic jack	□	□	□	□	□	□	■
Roller sections with 3D pendulum suspension	-	-	-	-	-	-	■
LED light	■	■	■	■	■	■	■
Cracker board	□	□	□	□	□	□	□
Cracker board with crust breaker	□	□	□	□	□	□	□
2-bullet harrow	□	□	□	□	□	□	□
2-bullet harrow and cracker board	□	□	□	□	□	-	-
3-bullet cultivator	□	□	□	-	-	-	□
Knife roller	-	□	-	-	□	-	-
Wheel track eradicator	□	□	□	□	□	□	□
Stone boxes 45L or 100L	□	□	□	□	□	□	□
Wheel upgrade	□	□	□	□	□	□	-
Cat. 3-point hitch	□	□	□	□	□	□	□
Pneumatic brakes or hydraulic brakes	□	□	□	□	□	□	□
Rubber-suspended bearings	□	□	□	□	□	□	-
DALBO seeding equipment	□	□	□	□	□	-	-
EU homologation	□	□	□	□	□	□	□

■ Standard □ Option - Not possible

DALBO®

Also available from DALBO



POWERROLL 3-sec 450-950



POWERROLL 5-sec 1030-1830



FRONT PRESSES 150-600



MAXIROLL 530-1230



MAXIROLL GREENLINE 630-830



MAXICUT 600-920



CULTIMAX 650-1000



ROLLOMAXIMUM 620-1240



ROLLOMASTER 300-600



TRIMAX 300-630



POWERCHAIN 500-1200



SUBSOILER M Profi

DALBO A/S, Bindeballevej 69, DK-7183 Randbøl
Tel.: +45 75 88 35 00, info@dalboagro.com, www.dalboagro.com